HIGH PERFORMANCE CLOSED DIE FORGINGS

PH. 216/477-4511

No

098623

filters. be wound

piping for testing te type filters may

DATE PAGE

FAX 216/477-2046 7/01/97

A CONTRACTOR OF THE PARTY OF TH

PURCHASE ORDER

**VENDOR** TO:

8529

PARSONS ENGINEERING -PF

19101 VILLAVIEW RD

STE 301

CLEVELAND

P.O. BOX 6902

SHIP TO:

CANTON, OHIO 44706

CANTON DROP FORGE

4575 SOUTHWAY STREET S.W.

P.O. BOX 6902

CANTON OH 44706

STOCK ROOM ATTN:

UNLESS OTHERWISE NOTED, SALES TAX DOES NOT APPLY ON ITEMS ORDERED

SHIP VIA:

ECCT HAV

4575 SOUTHWAY ST., S.W.

FREIGHT TERMS:

	F		n ege	00 Table		ř.
LINE NO.	DESCRIPTION/COMMENTS	U/M	PROMISED	QUANTITY	UNIT COST	TOTAL COST
	CONDENSATE TREATMENT TESTING ASSUMING ALL REASONABLE ADVANTAGE HAS BEEN TAKEN OF SUPPLIER BENCH TESTING \$6600.00 - PER PROPOSAL OF 6/12/97 & NAME "CONDENSATE TREATMENT TESTING"  KJH ESCROW KH1076  ATTACH APPLICABLE MATERIAL SAFETY DATA SHE TO THE PACKING LIST FOR THE PRODUCT(S) ORI NOTE: IF NOT ATTACHED, INDICATE REASON OR REVISION WAS SENT TO CDF. MATERIAL CANNOT WITHOUT MSDS OR EXPLANATION.  Purchase	ETS (MSDS) DERED. DATE LATEST MSDS		in the state of the contract of the state of the contract of t		.00

Terms and Conditions on reverse side are part of this Purchase Order

Acceptance - Unless otherwise stated herein, this order must be accepted by the Seller signing and returning the attached acknowledgment copy to Buyer within 10 days from the date of this order, and it is understood that the commencement of any work or the performance of any services hereunder by Seller shall constitute acceptance by Seller of this purchase order and

STEEL ORDERS:

1. Certified test reports in triplicate are to accompany steel shipments. Discount will be taken from date of receipt of goods or test reports, whichever is later.

Do not deviate from established producing practice in fulfulfing the requirements of this order.

INVOICE DAY OF SHIPMENT TO: CANTON DROP FORGE P.O. BOX 6902 CANTON, OH 44706

e different micron ratings will be filter housing is anticipated that filters of three dis 5, 25, and 100 pump, will install paper element type. I preliminary selection Filters to be tested OL

CDF001765



REMIT PAYMENT TO: File 91849 Los Angeles, CA 90074-1849 Attn: Accounts Receivables

Street Address: 19101 VILLAVIEW ROAD, SUITE 301 CLEVELAND, OHIO 44119

Tel: (216) 486-9005 Fax: (216) 486-6119

#### INVOICE

26)

JULY 8, 1997

CLIENT REF. :

INVOICE NO. :

00755152

PROJECT NO. :

731549-02

CLIENT NO. :

71275

TO: CANTON DROP FORGE, INC.

4575 SOUTHWAY STREET

CANTON, OHIO

44706

PLEASE REMIT TO:

PARSONS ENGINEERING SCIENCE, INC

FILE 91849

LOS ANGELES, CALIFORNIA

90074-1849

FOR: CANTON DROP FORGE, WBS 02000

ATTN: MR. KEITH HOUSEKNECHT

AUTHORIZATION: P.O. ?????? 98623

AMOUNT AUTHORIZED: \$6,600.00

BILLING PERIOD: PROJECT INITIATION THROUGH 6/27/97

	CUR. HOURS	CURRENT PERIOD THROUGH: 6/27/97	CUM. HOURS	CUMULATIV THROUGH	E-TO-DATE 6/27/97
WBS 02000 - FILTRATION TESTING DIRECT LABOR OH & PROFIT @1.95 X D.L.	10.5	\$386.86 \$754.38	10.5		\$386.86 \$754.38
SUBTOTAL:		\$1,141.24		-	\$1,141.24
TOTAL THIS INVOICE:		\$1,141.24			\$1,141.24

1

CLIENT REF .:

INVOICE NO.: 00755152
PROJECT NO.: 731549-02
CLIENT NO.: 71275
FORMAT NAME: SBLRLBR15C

		ADJ.	REGULAR	0/T	TOTAL	BILLING	LABOR	PREMIUM
	EMPLOYEE NAME	DATE	HOURS	HOURS	HOURS	RATE	BILLING	BILLING
30	SENIOR SPECIALIST I							
	CAROL M BOWERS		.50		.50	86.38	43.19	
	CLASSIFICATION TOTALS	3	.50		.50		43.19	
90	PRINC ENG/SCIENTIST I							
	MICHAEL R LEFFLER		10.00		10.00	109.80	1,098.05	
	CLASSIFICATION TOTAL	5	10.00		10.00		1,098.05	
	TOTAL LABOR BILLING		10.50		10.50		1,141.24	

PAGE:

1

CLIENT REF.:

INVOICE NO.: 00755152
PROJECT NO.: 731549-02
CLIENT NO.: 71275

FORMAT NAME: SBLRLBR11C

W/E DATE EMPLOYEE NAME	EMPLOYEE CLASSIFICATION	ADJ. DATE RATE	REGULAR HOURS	O/T HOURS	TOTAL HOURS
02000 FILTRATION TESTING					
6/27/97 MICHAEL R LEFFLER	PRINC ENG/SCIENTIST I	109.80	10.00		10.00
6/27/97 CAROL M BOWERS	SENIOR SPECIALIST I	86.38	.50		.50
ITEM TOTALS			10.50		10.50
TOTAL LABOR HOURS	•		10.50		10.50



REMIT PAYMENT TO: File 91849 Los Angeles, CA 90074-1849 Attn: Accounts Receivables

Street Address: 19101 VILLAVIEW ROAD, SUITE 301 CLEVELAND, OHIO 44119

Tel: (216) 486-9005 Fax: (216) 486-6119

#### INVOICE

JULY 8, 1997

CLIENT REF. :

INVOICE NO. :

00755152

PROJECT NO. :

731549-02

CLIENT NO. :

71275

TO: CANTON DROP FORGE, INC.

4575 SOUTHWAY STREET

CANTON, OHIO

44706

PLEASE REMIT TO:

PARSONS ENGINEERING SCIENCE, INC

FILE 91849

LOS ANGELES, CALIFORNIA

90074-1849

FOR: CANTON DROP FORGE, WBS 02000

ATTN: MR. KEITH HOUSEKNECHT

AUTHORIZATION: P.O. ?????? AMOUNT AUTHORIZED: \$6,600.00

BILLING PERIOD: PROJECT INITIATION THROUGH 6/27/97

	CUR.	CURRENT	NT PERIOD	CUM.	CUMULATIVE-TO-DATE	
	HOURS	THROUGH	6/27/97	HOURS	THROUGH	6/27/97
WBS 02000 - FILTRATION TESTING						_ "
DIRECT LABOR	10.5		\$386.86	10.5		\$386.86
OH & PROFIT @1.95 X D.L.			\$754.38			\$754.38
SUBTOTAL:		\$	1,141.24		2	\$1,141.24
TOTAL THIS INVOICE:		\$	1,141.24		m i	\$1,141.24
						*****

1

DETAIL OF PROFESSIONAL SERVICES FOR THE PERIOD ENDING 6/27/97

CLIENT REF .:

INVOICE NO.: 00755152 PROJECT NO.: 731549-02 CLIENT NO..: 71275 FORMAT NAME: SBLRLBR15C

		ADJ.	REGULAR	0/T	TOTAL	BILLING	LABOR	PREMIUM
	EMPLOYEE NAME	DATE	HOURS	HOURS	HOURS	RATE	BILLING	BILLING
			*					
30	SENIOR SPECIALIST I							
	CAROL M BOWERS		.50		.50	86.38	43.19	
	CLASSIFICATION TOTALS		.50		.50		43.19	
90	PRINC ENG/SCIENTIST I			•				
	MICHAEL R LEFFLER		10,00		10.00	109.80	1,098.05	
	CLASSIFICATION TOTALS		10.00		10.00		1,098.05	
	TOTAL LABOR BILLING		10.50		10.50		1,141.24	

1

CLIENT REF.:

INVOICE NO.: 00755152
PROJECT NO.: 731549-02
CLIENT NO..: 71275

FORMAT NAME: SBLRLBR11C

W/E DATE EMPLOYEE NAME	EMPLOYEE CLASSIFICATION	ADJ. DATE RATE	REGULAR HOURS	O/T HOURS	TOTAL HOURS
02000 FILTRATION TESTING					٠
6/27/97 MICHAEL R LEFFLER 6/27/97 CAROL M BOWERS ITEM TOTALS	PRINC ENG/SCIENTIST I SENIOR SPECIALIST I	109.80 86.38	10.00 .50 10.50		10.00 .50 10.50
TOTAL LABOR HOURS			10.50		10.50

REMIT PAYMENT TO: File 91849 Los Angeles, CA 90074-1849 Attn: Accounts Receivables

Street Address: 19101 VILLAVIEW ROAD, SUITE 301 CLEVELAND, OHIO 44119

Tel: (216) 486-9005 Fax: (216) 486-6119

INVOICE

2(6)

AUGUST 8, 1997

CLIENT REF. :

INVOICE NO. :

00802112

PROJECT NO. :

731549-02

CLIENT NO. :

71275

TO: CANTON DROP FORGE, INC.

4575 SOUTHWAY STREET

CANTON, OHIO

44706

PLEASE REMIT TO:

PARSONS ENGINEERING SCIENCE, INC

FILE 91849

LOS ANGELES, CALIFORNIA

90074-1849

FOR: CANTON DROP FORGE, WBS 02000

ATTN: MR. KEITH HOUSEKNECHT

AUTHORIZATION: P.O. 98623
AMOUNT AUTHORIZED: \$6,600.00

BILLING PERIOD: 6/28/97 THROUGH 7/25/97

	CUR.	CURRENT PERIOD	CUM.	CUMULATIVE-TO-DATE	
	HOURS	THROUGH 7/25/97	HOURS	THROUGH 7/25/97	
¥	-		1		
WBS 02000 - FILTRATION TESTING					
DIRECT LABOR	39.0	\$1,307.72	49.5	\$1,694.58	
OH & PROFIT @1.95 X D.L.		\$2,550.06		\$3,304.44	
ODCS WITHOUT HANDLING		\$46.48		\$46.48	
SUBTOTAL:	v	\$3,904.26		\$5,045.50	
TOTAL THIS INVOICE:		\$3,904.26		\$5,045.50	

#### DETAIL OF OTHER DIRECT COSTS FOR THE PERIOD ENDING 7/25/97

BY JOB/WBS/COST CODE

CLIENT REF.:

INVOICE NO.: 00802112 PROJECT NO.: 731549-02 CLIENT NO..: 71275 FORMAT NAME: SBLRODCWTT

	EQUIP/	•		•	***		
REF	VEND		INVOICE	DATE		BATCH	
NO.	NO.	NAME	DATE	WORKED	DESCRIPTION	NO.	TNUOMA
721540	CAMBON DOOD F	SORGE MAGRICULTURE		mu			
/31549	CANTON DROP F	ORGE, WASTEWATER					
0200	00 FILTRATION	TESTING					
	9212 AUTOMOBI	LE MILEAGE					
0797035	05 40953 MICHAEI	L R LEFFLER	7/04/97		•	389	44.33
2.3.700		·	.,, -		ACCOUNT TOTAL		44.33
	9543 POSTAGE						
	00052			7/18/97	POSTAGE	86	.55
	77000				ACCOUNT TOTAL	•	.55
	9551 COPIER	CHARGES					
	30270			7/18/97	COPIER CHARGES	94	.80
	30270			7/18/97	COPIER CHARGES	96	.50
	30270			7/18/97	COPIER CHARGES	96	.30
					ACCOUNT TOTAL		1.60
					FILTRATION TESTING		46.48
					JOB 731549 TOTAL		46.48
			•	TOTAL,	OTHER DIRECT COSTS		46.48

PAGE:

1



REMIT PAYMENT TO: File 91849 Los Angeles, CA 90074-1849 Attn: Accounts Receivables

Street Address: 19101 VILLAVIEW ROAD, SUITE 301 CLEVELAND, OHIO 44119

Tel: (216) 486-9005 Fax: (216) 486-6119

INVOICE

26

AUGUST 8, 1997

CLIENT REF. :

INVOICE NO. :

00802112

PROJECT NO. :

731549-02

CLIENT NO. :

71275

TO: CANTON DROP FORGE, INC.

4575 SOUTHWAY STREET

CANTON, OHIO

44706

PLEASE REMIT TO:

PARSONS ENGINEERING SCIENCE, INC

FILE 91849

LOS ANGELES, CALIFORNIA

90074-1849

FOR: CANTON DROP FORGE, WBS 02000 AUTHORIZATION: P.O. 98623

ATTN: MR. KEITH HOUSEKNECHT

AMOUNT AUTHORIZED: \$6,600.00

BILLING PERIOD: 6/28/97 THROUGH 7/25/97

	CUR. HOURS	CURRENT PERIOD THROUGH 7/25/97	CUM. HOURS	CUMULATIVE-TO-DATE THROUGH 7/25/97
WBS 02000 - FILTRATION TESTING				
DIRECT LABOR	39.0	\$1,307.72	49.5	\$1,694.58
OH & PROFIT @1.95 X D.L.		\$2,550.06		\$3,304.44
ODCS WITHOUT HANDLING		\$46.48		\$46.48
				AF 045 F0
SUBTOTAL:		\$3,904.26		\$5,045.50
TOTAL THIS INVOICE:		\$3,904.26	2	\$5,045.50

1

CLIENT REF.:

INVOICE NO.: 00802112
PROJECT NO.: 731549-02
CLIENT NO.: 71275
FORMAT NAME: SBLRLBR15C

		ADJ.	REGULAR	O/T	TOTAL	BILLING	LABOR	PREMIUM
	EMPLOYEE NAME	DATE	HOURS	HOURS	HOURS	RATE	BILLING	BILLING
					<b></b>		.=	
35	SPVG SPECIALIST II							
	MARK W STRAUB		2,00		2.00	55.01	110.04	
	CLASSIFICATION TOTALS		2.00		2.00		110.04	
					•			
55	STAFF ENGR/SCIENTIST II		•					
	A DAY OF THE WAR				1 50	40.70	61.18	
	ADAM C TUCKER	•	1.50			40.79	61.18	
	CLASSIFICATION TOTALS	<b>!</b>	1.50		1.50		61,18	
70	SR ENGINEER/SCIENTIST I							
	JOSEPH D PETERLIN		4.00		4.00	56.92	227.68	
	CLASSIFICATION TOTALS	3	4.00		4.00		227.68	
90	PRINC ENG/SCIENTIST I							
	MICHAEL R LEFFLER		31.50		31.50	109.80	3,458.88	
	CLASSIFICATION TOTAL	S	31.50	•	31.50		3,458.88	
							-,	
	TOTAL LABOR BILLING		39.00		39.00		3,857.78	

PAGE:

1

CLIENT REF .:

INVOICE NO.: 00802112
PROJECT NO.: 731549-02
CLIENT NO.: 71275
FORMAT NAME: SBLRLBR11C

			ADJ.	REGULAR	0/T	TOTAL
W/E DATE	EMPLOYEE NAME	EMPLOYEE CLASSIFICATION	DATE RATE	HOURS	HOURS	HOURS
020	00 FILTRATION TESTING	•				
7/04/97	MICHAEL R LEFFLER	PRINC ENG/SCIENTIST I	109.80	9.00		9.00
7/11/97	MICHAEL R LEFFLER	PRINC ENG/SCIENTIST I	109.80	7.00		7.00
7/18/97	MICHAEL R LEFFLER	PRINC ENG/SCIENTIST I	109.80	3.00		3.00
7/25/97	MICHAEL R LEFFLER	PRINC ENG/SCIENTIST I	109.80	12.50		12.50
7/25/97	MARK W STRAUB	SPVG SPECIALIST II	55.00	2.00		2.00
7/25/97	JOSEPH D PETERLIN	SR ENGINEER/SCIENTIST I	56.92	4.00		4.00
7/25/97	ADAM C TUCKER	STAFF ENGR/SCIENTIST II	40.79	1.50		1.50
	ITEM TOTALS			39.00		39.00
	TOTAL LABOR HOURS			39.00		39.00

PAGE:

DETAIL OF OTHER DIRECT COSTS FOR THE PERIOD ENDING 7/25/97

BY WBS/COST CODE

INVOICE NO.: 00802112 PROJECT NO.: 731549-02

CLIENT NO..: 71275

FORMAT NAME: SBLRFODC03

REF:

REFERENCE NUMBER			DESCRIPTION OF EXPENSES		
			*		
02000:	FILTRAȚION	TESTING			
				44.25	
	9210		TRAVEL	44.33	
	9540		FREIGHT/EXPRESS/POSTAGE	.55	
	9550		REPRODUCTION CHARGES	1.60	
	RATION TESTING	46.48			
			GRAND TOTAL OTHER DIRECT COSTS	46.48	

## DETAIL OF OTHER DIRECT COSTS FOR THE PERIOD ENDING 7/25/97 BY JOB/WBS/COST CODE

PAGE:

CLIENT REF.:

INVOICE NO.: 00802112 PROJECT NO.: 731549-02 CLIENT NO..: 71275 FORMAT NAME: SBLRODCWIT

	EQUIP/						
REF	VEND		INVOICE	DATE		BATCH	
NO.	NO.	NAME	DATE	WORKED	DESCRIPTION	NO.	AMOUNT
731549	CANTON DROP	FORGE, WASTEWATER					
0200	00 FILTRATIO	N TESTING					
	9212 AUTOMO	BILE MILEAGE					
0797035	05 40953 MICHA	AEL R LEFFLER	7/04/97			389	44.33
					ACCOUNT TOTAL	•	44.33
	9543 POSTA	GE				·	
	00052			7/18/97	POSTAGE	86	.55
					ACCOUNT TOTAL	.*	.55
	9551 COPIE	R CHARGES				•	
	30270			7/18/97	7 COPIER CHARGES	94	.80
	30270			7/18/9	7 COPIER CHARGES	96	.50
	30270			7/18/9	7 COPIER CHARGES	96	.30
					ACCOUNT TOTAL		1.60
					FILTRATION TESTING		46.48
					JOB 731549 TOTAL		46.48
		~		TOTAL,	OTHER DIRECT COSTS		46.48

A UNIT OF PARSONS INFRASTRUCTURE & TECHNOLOGY GROUP INC

19101 Villaview Road, Suite 301 • Cleveland, Ohio 44119 • (216) 486-9005 • Fax (216) 486-6119 PARESCL/697/Dee/MRL4-13

12 June 1997

1(0)

Mr. Keith Houseknecht Manager, Plant Engineering CANTON DROP FORGE, INC. 4575 Southway Street Canton, Ohio 44706

Subject:

Condensate Treatment Testing

Dear Mr. Houseknecht:

Per our telephone conversation of 10 June 1997, Parsons Engineering Science (Parsons ES) is pleased to submit this proposal for further testing to establish design criteria for a condensate treatment system for Canton Drop Forge. Our preliminary investigation as reported to you in the draft report (Canton Drop Forge Process Water and Wastewater Recycling/Treatment Investigation Summary Report) indicated that conventional filtration may be sufficient to reduce the oil and grease in the condensate to satisfactory levels for discharge to the sanitary sewer or even for reuse in the hot process softener (HPS). Although the qualitative filtration testing was very promising, the quantitative test results were suspect because of the reported low influent oil and grease. Because of its simplicity, low capital cost, and minimal operations/maintenance requirements the direct filtration option deserves further exploration.

Parsons ES proposes to conduct further testing to:

- 1. Determine the filtrate flow rate:
- 2. Determine the effluent oil & grease obtainable by simple filtration
- 3. Project the probable filter life.

Establishing these parameters through on-site testing will provide a basis for deciding whether to discharge to the sanitary sewer or to the HPS and will provide the required information to design a full-scale system .

## Scope of Work

#### Flow Measurement

Parsons ES will measure the condensate flow using the "bucket and stopwatch" method. This will be accomplished by measuring the time to fill a calculated volume in the existing 1,500-gallon condensate tank, and/or measuring the time to fill a container of measured volume such as a 55-gallon drum. If practical, Parsons ES will devise a method to be used by Canton Drop Forge personnel to obtain flow measurements at different times to obtain more data on flow variation over time.

#### Filtration

Parsons ES will install a temporary pump, filter housing and piping for testing of filters. Filters to be tested will either be bag filters or cartridge type. Cartridge type filters may be wound or paper element type. It is anticipated that filters of three different micron ratings will be tested. A preliminary selection is 5, 25, and 100 microns. Oil and grease, suspended solids and



Mr. Keith Houseknecht, Manager, Plant Engineering CANTON DROP FORGE, INC. 12 June 1997 Page 2- Dee/MRLA-13

temperature measurements will be collected during the tests and the flow rate and pressure will be monitored.

## **Preliminary Testing Procedure**

Condensate will be pumped at a flow rate of approximately 5 gpm through the filter with the smallest micron rating. The test will be run for approximately one hour. The filter inlet and discharge pressure will be recorded at the beginning and end of the test and periodically throughout the test. A sample of the influent condensate will be collected near the beginning of the test and analyzed for oil & grease and suspended solids. Samples of the filter effluent will be collected near the beginning of the test and near the end of the test and analyzed for the same parameters. The condensate temperature will be checked and the flow rate through the filter will be measured at the beginning and end of the test. The test will be terminated early if the pressure drop through the filter becomes too great (approaches or exceeds the manufacturer's recommendations).

The same one-hour test will then be conducted using each of the other two filter sizes. Based on the flow and pressure drop data collected, and the visual appearance of the filtered condensate, Parsons ES will select the finest filter which appears to give satisfactory performance for further testing. The selected filter will be reinstalled in the filter housing, and run for approximately four hours or more to provide further information for projecting filter life. During the extended run, inlet and outlet pressures will be recorded, one additional inlet sample and two additional discharge samples will be collected for analysis, and the flow rate will be measured.

## Report

Parsons ES will prepare a letter report summarizing the results of the tests. Assuming filtration proves to be a viable alternative for treatment of the condensate, the report will include a conceptual design and cost estimate for a permanent system.

## Sequencing of Work

All flow measurements and filter testing will be performed on Tuesday through Thursday when the drop forges are in full operation. The following site visits are anticipated:

- 1. Engineer--One half day to collect data such as tank dimensions, piping arrangement, and other information required to set up flow measurement and filtration testing.
- 2. Engineer--One day to conduct flow measurements.
- 3. Technician--One half day to install filter testing equipment
- 4. Engineer--One day to conduct filtration tests.
- 5. Technician--One half day to dismantle testing equipment and to restore the system to pretest conditions.

Item one will occur shortly after receipt of a notice to proceed. After the necessary equipment has been obtained (approximately two to three weeks), Items 2 and 3 will occur on the same day and items 4 and 5 will occur on the following two days.

Laboratory analysis will take approximately two weeks. Allowing another week for preparation of a draft report brings the total schedule to approximately eight weeks from receipt of notice to proceed to delivery of the draft report.

Mr. Keith Houseknecht, Manager, Plant Engineering CANTON DROP FORGE, INC. 12 June 1997 Page 3- Dee/MRL4-13

#### Compensation

Parsons ES proposes to perform the services offered in this proposal on a "time and expenses, cost not-to-exceed" basis. Labor and expenses will be invoiced in accordance with the terms and conditions of our previously submitted (11 April 1997) Engineering Services Agreement (ESA). Parsons ES will not invoice Canton Drop Forge for more than \$6,600 without further authorization. This budget estimate assumes that the project can be initiated on or by 20 June 1997.

This not-to-exceed amount is based on the following:

Engineering--41 hours
Technician--8 hours
Laboratory Analysis--\$720
Equipment Rental/Purchase and ODCs--\$780

## Additional Work Required

It should be noted that the work of this proposal is essential to determining the final disposal of the condensate, but additional work will be required to complete the project. Assuming that the testing results are satisfactory and filtration is selected as the treatment method, additional efforts will be required to select and implement the final disposal method. If filtration performance is not satisfactory, further evaluation of other treatment methods will be required.

If a consistently low oil and grease content can be obtained from the filters, Canton Drop Forge may want to consider returning the water to the HPS. As we have discussed, some investigation should be conducted to determine the limitations on oil & grease and possibly other parameters in the feed water to the HPS and to assure that significant oil and grease carry-over to the boilers is not already occurring. If the treated condensate is not clean enough to consider as an HPS feed water, discharge to the sanitary sewer should be implemented. This will require discussions with the City and/or Ohio EPA to establish permitting requirements and applicable limits. Permit applications would then have to be filed. With either disposal option, the permanent filtration system would have to be designed and installed (or possibly modified if installed under the modified approach below) along with the discharge piping to the HPS or sanitary sewer.

#### Alternative Approach

The scope of work proposed above is per our discussion of 10 June 1997 and includes installation of a temporary filtration system for testing purposes. As we have previously noted, a permanent filtration system is not very expensive. Canton Drop Forge may prefer to install a permanent system at this time to save the costs of the temporary system. There is some risk to this approach in that if filtration does not prove to be the best option or even a viable option, Canton Drop Forge will have purchased and installed equipment which has no further use. The preliminary testing results indicate that filtration can provide sufficient oil and grease removal, but the life of the filter cartridges cannot be predicted from the laboratory tests conducted.

Most of the proposed work is related to determining the condensate flow rate, selecting the proper filter size, and evaluating the performance of the filtration system. These items all need to be accomplished whether a temporary or permanent system is installed. The above proposal includes a total of \$1,500 for purchase/rental and installation of the temporary filtration system. Parsons ES estimates that the filter housing, pump, piping, valves, and gages required for a permanent system would cost \$2,000. Some additional engineering would be required to identify

Mr. Keith Houseknecht, Manager, Plant Engineering CANTON DROP FORGE, INC. 12 June 1997 Page 4- Dee/MRL4-13

the proper components to be purchased and to prepare a layout drawing to guide Canton Drop Forge in the installation of the components.

If Canton Drop Forge prefers to go directly to the permanent installation, our approach would change slightly. Referring to the Sequencing of Work section, Items 1 (information collection) and 2 (flow measurement) would be accomplished as described. Parsons ES would then design the system and specify the components for purchase and installation by Canton Drop Forge. After Canton Drop Forge has installed the system, Parsons ES will complete Item 4 (filtration tests) and prepare a final report. Items 3 and 5 (installation and removal of equipment by Parsons ES) are no longer required, but the additional task of designing the system is inserted.

For this approach, Parsons ES will complete the flow measurement and design within three weeks following the notice to proceed. There will then be a break in services while Canton Drop Forge purchases and installs the permanent system. It will then take another four weeks to perform the testing and prepare the draft report. Allowing six weeks for purchase and installation of equipment, the draft report would be delivered 13 weeks from receipt of the notice to proceed.

Parsons ES will perform the work described in this alternative approach for a not-to-exceed price of \$6,800. In addition to this, Canton Drop Forge will have to spend an estimated \$2,000 to purchase the system components and then install them. However, if the system performs satisfactorily, no further time or money will be required for design and installation of a permanent system. This system, however, will still be discharging to Pond 2, and further efforts will be required to implement the final disposal of the treated condensate as discussed above.

This not-to-exceed amount is based on the following:

Engineering--49 hours Drafting/Support Services--8 hours Laboratory Analysis--\$720 ODCs--\$275

If this proposal is acceptable to you, please issue a purchase order referencing this proposal and our ESA. Also indicate whether you are authorizing the proposed approach for \$6,600 or the alternative approach for \$6,800. This will serve as our authorization to proceed. Thank you for the opportunity to present this proposal. If you have any questions or wish to discuss this proposal, please do not hesitate to call.

Very truly yours,

PARSONS ENGINEERING SCIENCE

Wilson H. Rownd, P.E. Vice President/Manager.

Wilson H. Rowal Com

Michael R. Leffler, P.E.

Associate

WHR/MRL/dee cc: CMB (File)

98623

## PARSONS ENGINEERING SCIENCE, INC.

A UNIT OF PARSONS INFRASTRUCTURE & TECHNOLOGY GROUP INC

19101 Villaview Road, Suite 301 • Cloveland, Ohio 44119 • (216) 486-9005 • Fax (216) 486-6119 PARESCL/697/Dee/MRL4-13

12 June 1997

1 (c)

Mr. Keith Houseknecht Manager, Plant Engineering CANTON DROP FORGE, INC. 4575 Southway Street Canton, Ohio 44706

Subject:

Condensate Treatment Testing

Dear Mr. Houseknecht:

Per our telephone conversation of 10 June 1997, Parsons Engineering Science (Parsons ES) is pleased to submit this proposal for further testing to establish design criteria for a condensate treatment system for Canton Drop Forge. Our preliminary investigation as reported to you in the draft report (Canton Drop Forge Process Water and Wastewater Recycling/Treatment Investigation Summary Report) indicated that conventional filtration may be sufficient to reduce the oil and grease in the condensate to satisfactory levels for discharge to the sanitary sewer or even for reuse in the hot process softener (HPS). Although the qualitative filtration testing was very promising, the quantitative test results were suspect because of the reported low influent oil and grease. Because of its simplicity, low capital cost, and minimal operations/maintenance requirements the direct filtration option deserves further exploration.

Parsons ES proposes to conduct further testing to:

1. Determine the filtrate flow rate;

2. Determine the effluent oil & grease obtainable by simple filtration

3. Project the probable filter life.

Establishing these parameters through on-site testing will provide a basis for deciding whether to discharge to the sanitary sewer or to the HPS and will provide the required information to design a full-scale system.

Scope of Work

#### Flow Measurement

Parsons ES will measure the condensate flow using the "bucket and stopwatch" method. This will be accomplished by measuring the time to fill a calculated volume in the existing 1,500-gallon condensate tank, and/or measuring the time to fill a container of measured volume such as a 55-gallon drum. If practical, Parsons ES will devise a method to be used by Canton Drop Forge personnel to obtain flow measurements at different times to obtain more data on flow variation over time.

#### Filtration

Parsons ES will install a temporary pump, filter housing and piping for testing of filters. Filters to be tested will either be bag filters or cartridge type. Cartridge type filters may be wound or paper element type. It is anticipated that filters of three different micron ratings will be tested. A preliminary selection is 5, 25, and 100 microns. Oil and grease, suspended solids and



Mr. Keith Houseknocht, Manager, Plant Engineering CANTON DROP FORGE, INC. 12 June 1997 Page 2- Dec/MRLA-13

temperature measurements will be collected during the tests and the flow rate and pressure will be monitored.

## Preliminary Testing Procedure

Condensate will be pumped at a flow rate of approximately 5 gpm through the filter with the smallest micron rating. The test will be run for approximately one hour. The filter inlet and discharge pressure will be recorded at the beginning and end of the test and periodically throughout the test. A sample of the influent condensate will be collected near the beginning of the test and analyzed for oil & grease and suspended solids. Samples of the filter effluent will be collected near the beginning of the test and near the end of the test and analyzed for the same parameters. The condensate temperature will be checked and the flow rate through the filter will be measured at the beginning and end of the test. The test will be terminated early if the pressure drop through the filter becomes too great (approaches or exceeds the manufacturer's recommendations).

The same one-hour test will then be conducted using each of the other two filter sizes. Based on the flow and pressure drop data collected, and the visual appearance of the filtered condensate, Parsons ES will select the finest filter which appears to give satisfactory performance for further testing. The selected filter will be reinstalled in the filter housing, and run for approximately four hours or more to provide further information for projecting filter life. During the extended run, inlet and outlet pressures will be recorded, one additional inlet sample and two additional discharge samples will be collected for analysis, and the flow rate will be measured.

## Report

Parsons ES will prepare a letter report summarizing the results of the tests. Assuming filtration proves to be a viable alternative for treatment of the condensate, the report will include a conceptual design and cost estimate for a permanent system.

## Sequencing of Work

All flow measurements and filter testing will be performed on Tuesday through Thursday when the drop forges are in full operation. The following site visits are anticipated:

 Engineer—One half day to collect data such as tank dimensions, piping arrangement, and other information required to set up flow measurement and filtration testing.

Engineer--One day to conduct flow measurements.

3. Technician--One half day to install filter testing equipment4. Engineer--One day to conduct filtration tests.

5. Technician—One half day to dismantle testing equipment and to restore the system to pretest conditions.

Item one will occur shortly after receipt of a notice to proceed. After the necessary equipment has been obtained (approximately two to three weeks), Items 2 and 3 will occur on the same day and items 4 and 5 will occur on the following two days.

Laboratory analysis will take approximately two weeks. Allowing another week for preparation of a draft report brings the total schedule to approximately eight weeks from receipt of notice to proceed to delivery of the draft report.

Mr. Keith Houseknecht, Manager, Plant Engineering CANTON DROP FORGE, INC. 12 June 1997 Page 3- Dee/MRL4-13

#### Compensation

Parsons ES proposes to perform the services offered in this proposal on a "time and expenses, cost not-to-exceed" basis. Labor and expenses will be invoiced in accordance with the terms and conditions of our previously submitted (11 April 1997) Engineering Services Agreement (ESA). Parsons ES will not invoice Canton Drop Forge for more than \$6,600 without further authorization. This budget estimate assumes that the project can be initiated on or by 20 June 1997.

This not-to-exceed amount is based on the following:

Engineering—41 hours
Technician—8 hours
Laboratory Analysis—\$720
Equipment Rental/Purchase and ODCs—\$780

## Additional Work Required

It should be noted that the work of this proposal is essential to determining the final disposal of the condensate, but additional work will be required to complete the project. Assuming that the testing results are satisfactory and filtration is selected as the treatment method, additional efforts will be required to select and implement the final disposal method. If filtration performance is not satisfactory, further evaluation of other treatment methods will be required.

If a consistently low oil and grease content can be obtained from the filters, Canton Drop Forge may want to consider returning the water to the HPS. As we have discussed, some investigation should be conducted to determine the limitations on oil & grease and possibly other parameters in the feed water to the HPS and to assure that significant oil and grease carry-over to the boilers is not already occurring. If the treated condensate is not clean enough to consider as an HPS feed water, discharge to the sanitary sewer should be implemented. This will require discussions with the City and/or Ohio EPA to establish permitting requirements and applicable limits. Permit applications would then have to be filed. With either disposal option, the permanent filtration system would have to be designed and installed (or possibly modified if installed under the modified approach below) along with the discharge piping to the HPS or sanitary sewer.

## Alternative Approach

The scope of work proposed above is per our discussion of 10 June 1997 and includes installation of a temporary filtration system for testing purposes. As we have previously noted, a permanent filtration system is not very expensive. Canton Drop Forge may prefer to install a permanent system at this time to save the costs of the temporary system. There is some risk to this approach in that if filtration does not prove to be the best option or even a viable option, Canton Drop Forge will have purchased and installed equipment which has no further use. The preliminary testing results indicate that filtration can provide sufficient oil and grease removal, but the life of the filter cartridges cannot be predicted from the laboratory tests conducted.

Most of the proposed work is related to determining the condensate flow rate, selecting the proper filter size, and evaluating the performance of the filtration system. These items all need to be accomplished whether a temporary or permanent system is installed. The above proposal includes a total of \$1,500 for purchase/rental and installation of the temporary filtration system. Parsons ES estimates that the filter housing, pump, piping, valves, and gages required for a permanent system would cost \$2,000. Some additional engineering would be required to identify

06/12/97 THU 16:47 FAX 216 486 6119 PARSONS ES CLEVELAND

PARKONS ENGINEERING SCIENCE, INC.

Mr. Keith Houseknecht, Manager, Plant Engineering CANTON DROP FORGE, INC. 12 June 1997 Page 4- Dee/MRL4-13

the proper components to be purchased and to prepare a layout drawing to guide Canton Drop Forge in the installation of the components.

If Canton Drop Forge prefers to go directly to the permanent installation, our approach would change slightly. Referring to the Sequencing of Work section, Items I (information collection) and 2 (flow measurement) would be accomplished as described. Parsons ES would then design the system and specify the components for purchase and installation by Canton Drop Forge. After Canton Drop Forge has installed the system, Parsons ES will complete Item 4 (filtration tests) and prepare a final report. Items 3 and 5 (installation and removal of equipment by Parsons ES) are no longer required, but the additional task of designing the system is inserted.

For this approach, Parsons ES will complete the flow measurement and design within three weeks following the notice to proceed. There will then be a break in services while Canton Drop Forge purchases and installs the permanent system. It will then take another four weeks to perform the testing and prepare the draft report. Allowing six weeks for purchase and installation of equipment, the draft report would be delivered 13 weeks from receipt of the notice to proceed.

Parsons ES will perform the work described in this alternative approach for a not-toexceed price of \$6,800. In addition to this, Canton Drop Forge will have to spend an estimated \$2,000 to purchase the system components and then install them. However, if the system performs satisfactorily, no further time or money will be required for design and installation of a permanent system. This system, however, will still be discharging to Pond 2, and further efforts will be required to implement the final disposal of the treated condensate as discussed above.

This not-to-exceed amount is based on the following:

Engineering--49 hours Drafting/Support Services--8 hours Laboratory Analysis--\$720 ODCs--\$275

If this proposal is acceptable to you, please issue a purchase order referencing this proposal and our ESA. Also indicate whether you are authorizing the proposed approach for \$6,600 or the alternative approach for \$6,800. This will serve as our authorization to proceed. Thank you for the opportunity to present this proposal. If you have any questions or wish to discuss this proposal, please do not hesitate to call.

Very truly yours,

PARSONS ENGINEERING SCIENCE

Wilson H. Rownd, P.E. Vice President/Manager

Wilson H. Rowal

Michael R. Leffler, P.E.

Associate

WHR/MRL/dee cc: CMB (File)

216 486 6119

PARSONS ES CLEVELAND

## PARSONS ENGINEERING SCIENCE, INC.

A UNIT OF PARSONS INFRASTRUCTURE & TECHNOLOGY GROUP INC

19101 Villaview Road, Suile 301 . Cloveland, Ohio 44119 . (216) 486-9005 . Fax (216) 486-6119 PARESCL/697/Dee/MRL4-13

12 June 1997

Mr. Keith Houseknecht Manager, Plant Engineering CANTON DROP FORGE, INC. 4575 Southway Street Canton, Ohio 44706

Subject:

Condensate Treatment Testing

Dear Mr. Houseknecht:

SHOULDN'T COLPECTED TO STORE THE SON ATTOR MAJOR THE STORE THE STO Per our telephone conversation of 10 June 1997, Parsons Engineering Science (Parsons ES) is pleased to submit this proposal for further testing to establish design criteria for a condensate treatment system for Canton Drop Forge. Our preliminary investigation as reported report (Canton Drop Forge/Process Water and Wastewater to you in the draft Recycling/Treatment Investigation Summary Report ) indicated that conventional filtration may be sufficient to reduce the oil and grease in the condensate to satisfactory levels for discharge to the sanitary sewer or even for reuse in the hot process softener (HPS). Although the qualitative

Parsons ES proposes to conduct further testing to:

1. Determine the filtrate flow rate;

2. Determine the effluent oil & grease obtainable by simple filtration

3. Project the probable filter life. filtration testing was very promising, the quantitative test results were suspect because of the

3. Project the probable filter life.

Establishing these parameters through on-site testing will provide a basis for deciding whether to discharge to the sanitary sewer or to the HPS and will provide the required information to design a full-scale system.

## Scope of Work

#### Flow Measurement

Parsons ES will measure the condensate flow using the "bucket and stopwatch" method. This will be accomplished by measuring the time to fill a calculated volume in the existing 1,500gallon condensate tank, and/or measuring the time to fill a container of measured volume such as a 55-gallon drum. If practical, Parsons ES will devise a method to be used by Canton Drop Forge personnel to obtain flow measurements at different times to obtain more data on flow variation over time.

#### Filtration

Parsons ES will install a temporary pump, filter housing and piping for testing of filters. Filters to be tested will either be bag filters or cartridge type. Cartridge type filters may be wound or paper element type. It is anticipated that filters of three different micron ratings will be tested. A preliminary selection is 5, 25, and 100 microns. Oil and grease, suspended solids and



Mr. Keith Houseknocht, Manager, Plant Engineering CANTON DROP FORGE, INC. 12 June 1997 Page 2- Dee/MRL4-13

temperature measurements will be collected during the tests and the flow rate and pressure will be monitored.

## Preliminary Testing Procedure

Condensate will be pumped at a flow rate of approximately 5 gpm through the filter with the smallest micron rating. The test will be run for approximately one hour. The filter inlet and discharge pressure will be recorded at the beginning and end of the test and periodically throughout the test. A sample of the influent condensate will be collected near the beginning of the test and analyzed for oil & grease and suspended solids. Samples of the filter effluent will be collected near the beginning of the test and near the end of the test and analyzed for the same parameters. The condensate temperature will be checked and the flow rate through the filter will be measured at the beginning and end of the test. The test will be terminated early if the pressure drop through the filter becomes too great (approaches or exceeds the manufacturer's recommendations).

The same one-hour test will then be conducted using each of the other two filter sizes. Based on the flow and pressure drop data collected, and the visual appearance of the filtered condensate, Parsons ES will select the finest filter which appears to give satisfactory performance for further testing. The selected filter will be reinstalled in the filter housing, and run for approximately four hours or more to provide further information for projecting filter life. During the extended run, inlet and outlet pressures will be recorded, one additional inlet sample and two additional discharge samples will be collected for analysis, and the flow rate will be measured.

## Report

Parsons ES will prepare a letter report summarizing the results of the tests. Assuming filtration proves to be a viable alternative for treatment of the condensate, the report will include a conceptual design and cost estimate for a permanent system.

## Sequencing of Work

All flow measurements and filter testing will be performed on Tuesday through Thursday when the drop forges are in full operation. The following site visits are anticipated:

1. Engineer--One half day to collect data such as tank dimensions, piping arrangement, and other information required to set up flow measurement and filtration testing.

Engineer—One day to conduct flow measurements.

3. Technician-One half day to install filter testing equipment

4. Engineer-One day to conduct filtration tests.

5. Technician—One half day to dismantle testing equipment and to restore the system to pretest conditions.

Item one will occur shortly after receipt of a notice to proceed. After the necessary equipment has been obtained (approximately two to three weeks), Items 2 and 3 will occur on the same day and items 4 and 5 will occur on the following two days.

Laboratory analysis will take approximately two weeks. Allowing another week for preparation of a draft report brings the total schedule to approximately eight weeks from receipt of notice to proceed to delivery of the draft report.

Mr. Keith Houseknecht, Manager, Plant Engineering CANTON DROP FORGE, INC. 12 June 1997 Page 3- Dee/MRLA-13

#### Compensation

Parsons ES proposes to perform the services offered in this proposal on a "time and expenses, cost not-to-exceed" basis. Labor and expenses will be invoiced in accordance with the terms and conditions of our previously submitted (11 April 1997) Engineering Services Agreement (ESA). Parsons ES will not invoice Canton Drop Forge for more than \$6,600 without further authorization. This budget estimate assumes that the project can be initiated on or by 20 June 1997.

This not-to-exceed amount is based on the following:

Engineering-41 hours Technician--8 hours Laboratory Analysis--\$720 Equipment Rental/Purchase and ODCs--\$780

## Additional Work Required

It should be noted that the work of this proposal is essential to determining the final disposal of the condensate, but additional work will be required to complete the project. Assuming that the testing results are satisfactory and filtration is selected as the treatment method, additional efforts will be required to select and implement the final disposal method. If filtration performance is not satisfactory, further evaluation of other treatment methods will be required.

If a consistently low oil and grease content can be obtained from the filters. Canton Drop Forge may want to consider returning the water to the HPS. As we have discussed, some investigation should be conducted to determine the limitations on oil & grease and possibly other parameters in the feed water to the HPS and to assure that significant oil and grease carry-over to the boilers is not already occurring. If the treated condensate is not clean enough to consider as an HPS feed water, discharge to the sanitary sewer should be implemented. This will require discussions with the City and/or Ohio EPA to establish permitting requirements and applicable Permit applications would then have to be filed. With either disposal option, the permanent filtration system would have to be designed and installed (or possibly modified if installed under the modified approach below) along with the discharge piping to the HPS or sanitary sewer.

## Alternative Approach

The scope of work proposed above is per our discussion of 10 June 1997 and includes installation of a temporary filtration system for testing purposes. As we have previously noted, a permanent filtration system is not very expensive. Canton Drop Forge may prefer to install a permanent system at this time to save the costs of the temporary system. There is some risk to this approach in that if filtration does not prove to be the best option or even a viable option, Canton Drop Forge will have purchased and installed equipment which has no further use. The preliminary testing results indicate that filtration can provide sufficient oil and grease removal, but the life of the filter cartridges cannot be predicted from the laboratory tests conducted.

Most of the proposed work is related to determining the condensate flow rate, selecting the proper filter size, and evaluating the performance of the filtration system. These items all need to be accomplished whether a temporary or permanent system is installed. The above proposal includes a total of \$1,500 for purchase/rental and installation of the temporary filtration system. Parsons ES estimates that the filter housing, pump, piping, valves, and gages required for a permanent system would cost \$2,000. Some additional engineering would be required to identify

Mr. Keith Houseknecht, Manager, Plant Engineering CANTON DROP FORGE, INC. 12 June 1997 Page 4- Dee/MRL4-13

the proper components to be purchased and to prepare a layout drawing to guide Canton Drop Forge in the installation of the components.

If Canton Drop Forge prefers to go directly to the permanent installation, our approach would change slightly. Referring to the Sequencing of Work section, Items 1 (information collection) and 2 (flow measurement) would be accomplished as described. Parsons ES would then design the system and specify the components for purchase and installation by Canton Drop Forge. After Canton Drop Forge has installed the system, Parsons ES will complete Item 4 (filtration tests) and prepare a final report. Items 3 and 5 (installation and removal of equipment by Parsons ES) are no longer required, but the additional task of designing the system is inserted.

For this approach, Parsons ES will complete the flow measurement and design within three weeks following the notice to proceed. There will then be a break in services while Canton Drop Forge purchases and installs the permanent system. It will then take another four weeks to perform the testing and prepare the draft report. Allowing six weeks for purchase and installation of equipment, the draft report would be delivered 13 weeks from receipt of the notice to proceed.

Parsons ES will perform the work described in this alternative approach for a not-to-exceed price of \$6,800. In addition to this, Canton Drop Forge will have to spend an estimated \$2,000 to purchase the system components and then install them. However, if the system performs satisfactorily, no further time or money will be required for design and installation of a permanent system. This system, however, will still be discharging to Pond 2, and further efforts will be required to implement the final disposal of the treated condensate as discussed above.

This not-to-exceed amount is based on the following:

Engineering--49 hours
Drafting/Support Services--8 hours
Laboratory Analysis--\$720
ODCs--\$275

If this proposal is acceptable to you, please issue a purchase order referencing this proposal and our ESA. Also indicate whether you are authorizing the proposed approach for \$6,600 or the alternative approach for \$6,800. This will serve as our authorization to proceed. Thank you for the opportunity to present this proposal. If you have any questions or wish to discuss this proposal, please do not hesitate to call.

Very truly yours,

PARSONS ENGINEERING SCIENCE

Wilson H. Rownd, P.E. Wilson H. Rownd, P.E.

Vice President/Manager

Michael R. Leffler, P.E.

Associate

WHR/MRL/dee cc: CMB (File)